



HIP
อันดับ 1 เรื่องสินค้าและบริการ

HIP
รับประกันภัยสูงสุด 5 ล้านบาท

IP Camera

CMT9000F

2Mp IP Camera



จับตาทุกความเคลื่อนไหว

Features:

Camera	
Image sensor	2MP, 1/2.8" Sony ExmorCMOS sensor
core processor	ARM9 Architecture processor
operating system	Embedded LINUX
Effective Pixels	2 M
Image resolution	Main stream: 1080P(1920*1080); Second stream:D1(704*576)
Framerate	PAL: 1080P@25 F/S NTSC: 1080P@30 F/S
WDR	100db
Electronic Shutter	1/25S~1/10000S
Mini. Illumination	Color0.05 Lux @(F1.2, AGC ON) B/W0.01Lux @(F1.2, AGC ON); 0 Lux with IR
Day/Night	ICR
Videoparameters	Contrast, brightness, saturation can be adjusted independently
Image processing	Support 3D noise reduction, de-interlace, image enhancement, edge enhancement, backlight compensation, gamma adjustment
Lens	
Lens interface type	C/CS
Interface	
Video interface	1Vp-p Composite Output (75Ω/BNC)
Audio interface	1 channel input; 1 channel output
Alarm interface	1 channel input
Network Port	10/100MEthernet interface RJ45
Protocol	Onvif
Encode Mode	
Video Compression	H.264/MJPEG
Audio Compression	G.711/G.726/ADPCM
Encode type	BaseLine Profile/ Main Profile
Video Compression code rate	32K~8Mbps
Audio Compression code rate	8K~48Kbps
Others	
IE browser	Web server
Mobile	Support IOS/Android/WindowsMobile
Client	≤8
Local storage	Support MicroSD card, max 32G
Network protocol	P
IP address	Support static state IP address、DDNS
OSD character	Support character, time, support max 128 characters
Authority	4 level、128 users
System clock	Build-in clock, support external synchronization
Remote mamagement	Remote network upgrade
Intelligent alarm	Motion detection, Port alarm
General	
Ingress Protection	IP66
Operating Environment	-30℃~60℃, 0~95% RHG
Power Supply	DC 12V±10%
Power Consumption	5 W
Dimension	145mm×71mm×58mm
Weight	0.6 Kg



ISO9001:2008

